vimrc

```
set ts=2

set backspace=2

set number
set autowrite
set autoindent
set nowrap


hi Comment      term=none       ctermfg=gray    guifg=Gray
hi Keyword      term=bold       ctermfg=yellow  guifg=White
hi Constant     term=underline  ctermfg=cyan    guifg=Cyan
hi Identifier   term=underline  ctermfg=green   guifg=Yellow
hi Statement    term=bold       ctermfg=white   guifg=White
hi PreProc      term=underline  ctermfg=magenta guifg=Magenta
hi Type         term=underline  ctermfg=white   guifg=White
hi Special      term=bold       ctermfg=blue    guifg=#7f7fff
hi Nontext      term=bold       ctermfg=red     guifg=Red
hi Normal       guifg=Yellow    guibg=#00005F
hi Normal       ctermfg=darkgreen


hi Comment      cterm=none      gui=none
hi Constant     cterm=bold      gui=none
hi Identifier   cterm=none      gui=none
hi Statement    cterm=bold      gui=bold
hi PreProc      cterm=bold      gui=bold
hi Type         cterm=bold      gui=bold
hi Special      cterm=bold      gui=none
hi NonText      cterm=bold      gui=none
hi Keyword      cterm=bold      gui=none



set laststatus=2
set statusline=%F%m%r%h%w\ [ASCII=\%03.3b]\ [HEX=\%02.2B]\
[POS=%04l,%04v][%p%%]\ [LEN=%L]

syntax on

ab #T //TODO, kkv
ab #t //TODO:
ab #i //CODE INSPECTION:
```

vim, vimrc

From:
http://wiki.osll.ru/ - **Open Source & Linux Lab**

Permanent link:
http://wiki.osll.ru/doku.php/etc:blogs:kkv:vimrc

Last update: **2009/11/27 13:58**