

# Linux port for Xtensa

- Linux git tree: <https://github.com/jcmvbkbc/linux-xtensa>
- Build/test tools git tree: <https://github.com/jcmvbkbc/xtensa-linux-test>
- Toolchain build scripts/overlays git tree: <https://github.com/jcmvbkbc/xtensa-toolchain-build>
- [Patch review check list](#)
- [Patch/pull request check list](#)

## Phase 1

Goal: linux mainline contains the latest linux-xtensa updates, builds and works.

- compilable with latest GCC
- overlays to cover: FSF, dc232b, more TBD
- tests to pass: builds, boots, LTP
- boards to focus on: ISS, ML605
- configurations: UP, linux-next specific, more TBD

## Plan

- [+] Prepare for linux-next participation
  - [+] Make mainline build for ARCH=xtensa in defconfig, allnoconfig, allmodconfig
    - [+] fix remaining issues with allmodconfig
    - qemu needs proper handling for guest ioctls triggered via simcalls
  - [+] Make built images work (qemu, FSF)
- [+] Build userspace
- Automated build/test scripts
  - [+] build/test status/logs
  - expect script to run LTP
- Analyse reference tree
  - proper bugfixes
  - new cores (dc233c, test\_hifi\_c3, s\*)
  - new platforms (lx\*, ml605, s\*)
  - SMP and its fixes
  - XCC fixes
- [Issues](#)

## Work items

### SMP support

Done, in the mainline:

```
99d5040 xtensa: keep a3 and excsave1 on entry to exception handlers
```

```
5515daa xtensa: fix arch spinlock function names
6235153 xtensa: update clockevent setup for SMP
cbd1de2 xtensa: move built-in PIC to drivers/irqchip
26a8e96 xtensa: add MX irqchip
f615136 xtensa: add SMP support
49b424f xtensa: implement CPU hotplug
```

## Support for Tensilica FPGA boards

- [+] serial
- [+] ethernet
- [+] FLASH
- [-] audio

In the mainline:

```
0d456ba xtensa: add support for the XTFPGA boards
5584b4d xtensa: add XTFPGA DTS
```

## Atomics (arch/xtensa/include/asm/atomic.h, bitops.h, spinlock.h) and check for S32C1I

Merged in the eb0a9bf31fdbcee9463c0f42bf4a292ef149a7d, pick up from individual files.

Done, in the mainline:

```
2f6ea6a xtensa: display s32cli feature flag in cpuinfo
733536b xtensa: save and restore scompare1 SR on kernel entry
c622b29 xtensa: initialize atomctl SR
28570e8 xtensa: add trap_set_handler function
0027312 xtensa: add s32cli sanity check
219b1e4 xtensa: add s32cli-based atomic ops implementations
e5a9f6a xtensa: add s32cli-based bitops implementations
71872b5 xtensa: add s32cli-based spinlock implementations
599bf77 xtensa: fix mb and wmb definitions
```

## TIE coprocessors

23ae3f723c8996d47ef205e98cb7732bbde4775f

## Highmem

Non-functional. Doing from scratch.

## Interrupt management

Done, in the mainline:

```
2206d5d xtensa: add IRQ domains support
```

## Medium level interrupts in less hacky way

```
489fb47c75772e3a41ef3e988eb0c0e512592085
```

Done, in the mainline:

```
2d1c645 xtensa: dispatch medium-priority interrupts  
895666a xtensa: disable IRQs while IRQ handler is running
```

## Device trees support

Done, in the mainline:

```
da844a8 xtensa: add device trees support
```

## MMU v3

Done, in the mainline:

```
e85e335 xtensa: add MMU v3 support  
93e294a xtensa: document MMUv3 setup sequence
```

## ptrace (support latest GDB)

```
617244763e19a4eebb4fabe41ba56eb1ccbdb049, 23ae3f723c8996d47ef205e98cb7732bbde4775f,  
ff1b10f85a1176d1eb8df433434b717f6f0841d4 (already upstream),  
a2b61af3328025d6069e8bf9ff36f5288e11dba9
```

## Support for building with XCC

### simdisk

```
1a955825662fa378d447b91485d9fe2438124b0a, 8bcbc3adb5c5bfd96078c1e68916be859c832d
```

Done, in the mainline:

```
b6c7e87 xtensa: ISS: add host file-based simulated disk
```

## Various fixes made for debuggability

### oprofile

```
8c502ca703956e56bf191774e4169752f0f71c8e,7dd1d39e70769f2dd7a6a508d58b187ed8d1cb95
```

Done, in the mainline:

```
e6ffe17 xtensa: add support for oprofile  
74f5bf0 xtensa: fix oprofile building as module
```

### Generic kernel\_thread & friends

Done, in the mainline:

```
3306a72 xtensa: switch to generic kernel_thread()  
f0a1bf0 xtensa: switch to generic kernel_execve()  
dc241f2 xtensa: switch to generic sys_execve()
```

### Cache aliasing aware mmap

Done, in the mainline:

```
de73b6b xtensa: avoid mmap cache aliasing
```

From:  
<http://wiki.osll.ru/> - **Open Source & Linux Lab**

Permanent link:  
<http://wiki.osll.ru/doku.php/etc:users:jcmvbkbc:linux-xtensa?rev=1397084320>

Last update: **2014/04/10 02:58**

