Доработки библиотеки hpx

> Вырастает из темы: *Доработки hpx*

p0233 – 2017-10-15 HP

p0566 – 2018-05-06 Proposed wording HP and RCU

p1121 – 2019-01-20 Proposed wording and interface for HP

folly – Реализация, приближенная к p0566. Использует части библиотеки folly(SingletonThreadLocal, SingletonManager, folly:Executor).

libcds – Другая реализация HP.

folly умеет использовать не только thread_local, libcds использует только thread_local storage.

В p0233 написано “Due to the performance advantages of using TLS, the library implementation should allow the programmer to choose implementation paths that benefit from TLS when suitable, and avoid TLS when incompatible with the use case.”

libcds:

```
cds::Initialize(); once
cds::gc::HP hpGC; once
cds::threading::Manager::attachThread(); every thread
cds::threading::Manager::detachThread(); every thread
```

http://libcds.sourceforge.net/doc/cds-api/index.html#cds_how_to_use

Не умеет в разные HP_domain, умеет только в собственный thread_local tls, не особо гибкий. Хотя умеет в

```
    set_memory_allocator(
          void* ( *alloc_func )( size_t size ),   ///< \p malloc() function
          void( *free_func )( void * p )  )
```

class HP – главный класс, Before use any HP-related class you must initialize \p %HP by contructing \p %cds::gc::HP object in beginning of your \p main().

class Guard – A guard is a hazard pointer. Additionally, the Guard class manages allocation and deallocation of the hazard pointer.

Guard::protect()

From:
http://wiki.osll.ru/ - **Open Source & Linux Lab**

Permanent link:
http://wiki.osll.ru/doku.php/projects:hpx:start?rev=1589464638

Last update: **2020/05/14 16:57**